



## Product Information

### ULTRA LOW SULFUR No. 2 AMOCO DIESEL FUEL

#### PRODUCT DESCRIPTION

Ultra Low Sulfur (ULS) No. 2 Amoco Diesel Fuel is refined from selected crudes, and is carefully blended to produce a high quality fuel. ULS No. 2 Amoco Diesel meets the needs of most automotive, marine and stationary engine applications. It also meets EPA on-road requirements for sulfur content.

#### APPLICATION

Ultra Low Sulfur No. 2 Amoco Diesel Fuel is recommended for use in all on- or off-road heavy duty trucks, automotive, transit bus, marine and stationary diesel engine applications requiring a No. 2 diesel fuel.

#### FEATURES

**Lubricity** – ULS No. 2 Amoco Diesel Fuel is additized to ensure it has the lubricity to protect diesel fuel injection systems.

**Stability** – ULS No. 2 Amoco Diesel Fuel is blended and additized to ensure good storage stability and to resist rust deposit formation in fuel systems.

**Low Pour Point** – ULS No. 2 Amoco Diesel Fuel is additized to reduce pour point which aids in storage and handling at low temperatures.

**Ultra Low Sulfur Content** – ULS No. 2 Amoco Diesel Fuel contains a maximum of 15 parts per million (ppm) sulfur.

## ULTRA-LOW SULFUR HIGHWAY DIESEL FUEL

(15 ppm Sulfur Maximum)

### WARNING

*Required* for use in all model year 2007 and later highway diesel vehicles and engines.

Recommended for use in all diesel vehicles and engines.



## Product Information – Ultra Low Sulfur No. 2 Amoco Diesel Fuel

<b><u>PROPERTY</u></b>	<b><u>TEST METHOD</u></b>	<b><u>LIMIT</u></b>
Ash, wt. %, max.	D482	0.01
Biodiesel Content, vol. <sup>(1)</sup>	D7371	0 – 5
Cetane Index, min.	D976	40
Cetane Number, min.	D613	40
Cloud Point, °F, max. <sup>(2)</sup>	D2500	
Summer (3/1 – 9/30)		+20
Winter (10/1 – 2/29)	+15	
Color, ASTM, max.	D1500	2.5
Conductivity @ 20 °C, cu, min.	D2624	50
Copper Corrosion, 3 hrs @122 °F, max.	D130	3
Distillation, °F	D86	
Temp.@ 90%, recovered		540 – 640
Temp.@ Endpoint, max.		690
Flash Point, °F, min.	D56, D93	125
Gravity, °API, min.	D287	30
Lubricity, HFRR @ 60 °C, micron, max.	D6079	520
Pour Point, °F, max. <sup>(2)</sup>	D97	
Summer (3/1 – 9/30)		+10
Winter (10/1 – 2/29)	0	
Stability, meet one of the following		
Thermal, % Reflect., 90 minutes, min.	D6468	75
Oxidation, mg/100mL, max.	D2274	2.5
Sulfur, total, ppm, max.	D5453, D7039	15
Viscosity, cSt @ 40 °C, min.	D445	1.9 – 3.4
Water & Sediment, vol.%, max.	D2709	0.05

### Notes

(1) When required by local or state law. Biodiesel blendstock conforms to ASTM D6751

(2) Cloud and pour point values may vary with region.

Call Quality & Technical Service for details.

For further information on Amoco fuels, contact:

BP Quality & Technical Service  
 Phone: 1-800-841-5255  
 BP Naperville Complex  
 150 West Warrenville Road  
 Naperville, Illinois 60563  
 Website: www.BP.com

02/19/2008